

Crimp specification							
Type Document	Crimp Specification	Revised /Edition	A				
Date Issued:	2021/04/19	2021/04/19 Data Revised:					
Subject: 1511T	Issued By:						
1.50mr	Engineering Dept.						

## Description:


Height and width of conductor crimp core should be set as required.

(conductor crimp height and width of conductor barrel)

According to the external diameter and the type of electric wire, the width of crimped sheath shall be adjusted, wire won't be easily taken off from contact nor too much crimped.

(Crimped width of insulation barrel)

## Position Graph:



#### Note:

- 1. Conductor crimp width. W1
- 2. Conductor crimp height. H1
- 3. Insulator crimp width. W2
- 4. Insulator crimp height. H2
- 5. Conductor wire shall be dimension long (mm) out A.
- 6. Naked part of sheathed wire must be located in the vicinity of center B.
- 7. The Crimp mouth must be equipped like bell.



Crimp specification							
Type Document	Crimp Specification	Revised /Edition	А				
Date Issued:	2021/04/19	Data Revised:	2021/04/19				
Subject: 1511T	Issued By:						
1.50mm	Engineering Dept.						

# Requirement:

Subject:UL1061 or equivalent type electric wire								
AWG#	Conductor (mm²)	Insulation Diameter Insulator skins length (Dim .B) mm		Copper wire leakage size (Dim .A) mm	Dim. L1 (mm) out			
#28~#24	0.08mm²~0.205mm²	1.10mm(max)	0.3	30mm~0.70mm 0.10mm~0.40mm		1.10mm~1.60mm		
Wire Gauge	Conductor Crimp Area			Insulator Crimp Area		Terminal Tensile		
(AWG#)	Width (W1)	Height(H1)		Width (W2)	Height(H2)	Strength		
#28		0.55±0.03mm			1.20±0.05mm	1.00kgf		
#26	0.94±0.03mm	0.62±0.03mr	n	1.20±0.05mm	1.35±0.05mm	2.00kgf		
#24		0.68±0.03mi	m		1.45±0.05mm	3.00kgf		

### Remarks

- 1. Unalike equipment and crimp reel molds skill facility or not shall be difference to result in dissimilar.
- 2. This crimping specification is not limited to material changes.

Signature: \_\_\_\_\_\_ENG

Dongguan SESO Technology Co.,Ltd